

TOPOI OF AUTOMATA II: HYPERCONNECTED GEOMETRIC MORPHISMS AND SYNTACTIC TOPOI

RYUYA HORA

ABSTRACT. For a hyperconnected geometric morphism from the topos of Σ -sets, we formulate language recognition using the local state classifier. For a language class C , we construct the associated syntactic Grothendieck topos $\mathcal{T}(C)$.

Preprint v0.1 (15 August 2026). This work is in progress and does not constitute the complete version of the project.

CONTENTS

1. Introduction	1
2. Hyperconnected geometric morphisms from $\Sigma\text{-Set}$	2
2.1. Hyperconnected geometric morphisms	2
2.2. Local state classifiers	2
2.3. The local state classifier of $\Sigma\text{-Set}$	3
3. Language recognition and syntactic topoi	4
3.1. Language recognition by a hyperconnected geometric morphism	4
3.2. The syntactic Grothendieck topos associated with a language class	4
Acknowledgements	5
Use of AI	5
References	5

1. INTRODUCTION

Let Σ be a finite alphabet and Σ^* its free monoid. We write $\Sigma\text{-Set}$ for the category of right Σ^* -actions and equivariant maps. The set of languages $\mathcal{L} = \mathcal{P}(\Sigma^*)$ is a right Σ^* -set with action

$$L \cdot w = w^{-1}L = \{v \in \Sigma^* \mid wv \in L\}.$$

A right Σ^* -set Q is **orbit-finite** if $\{q \cdot w \mid w \in \Sigma^*\}$ is finite for every $q \in Q$. We denote the full subcategory of orbit-finite Σ -sets by $\Sigma\text{-Set}_{\text{o.f.}}$. These conventions and constructions are those of [Hor24b].

As discussed in [Hor24b], the hyperconnected geometric morphism

$$\Sigma\text{-Set} \xrightarrow{h} \Sigma\text{-Set}_{\text{o.f.}}$$

2020 *Mathematics Subject Classification.* 18F10, 68Q70, 18B20.

Key words and phrases. Automaton, topos, language, hyperconnected geometric morphism, local state classifier.

ZEN University. ryuya_hora@zen.ac.jp.

plays a central role in our theory of regular languages. This work considers other hyperconnected geometric morphisms

$$\begin{array}{ccc} & & \mathcal{E} \\ & \nearrow & \\ \Sigma\text{-}\mathbf{Set} & \longrightarrow & \mathcal{F} \\ & \searrow & \\ & & \mathcal{G} \end{array}$$

and their associated classes of languages.

2. HYPERCONNECTED GEOMETRIC MORPHISMS FROM $\Sigma\text{-}\mathbf{Set}$

2.1. Hyperconnected geometric morphisms. See [Joh02; Joh81] for the detailed definitions of hyperconnected geometric morphisms.

Definition 2.1 (Hyperconnected geometric morphisms). A geometric morphism $f: \mathcal{E} \rightarrow \mathcal{F}$ is **hyperconnected** if f^* is fully faithful and f satisfies the following equivalent conditions:

- The essential image of f^* is closed under taking subquotients.
- The essential image of f^* is closed under taking subobjects.
- The essential image of f^* is closed under taking quotient objects.
- The counit $\epsilon: f^* f_* \Rightarrow \text{id}_{\mathcal{E}}$ is monic.

Since f^* for a hyperconnected geometric morphism $f: \mathcal{E} \rightarrow \mathcal{F}$ is fully faithful, the codomain topos $\mathcal{F}$ can be regarded as a full subcategory of the domain topos $\mathcal{E}$. If we regard it as a full subcategory, we call it a **hyperconnected quotient**, according to the terminology in [Law07, section VII].

We consider the order of equivalence classes of hyperconnected quotients induced by inclusion of the essential images of their inverse-image functors in $\mathcal{E}$.

Proposition 2.2. *For any Grothendieck topos $\mathcal{E}$, the partially ordered class of equivalence classes of hyperconnected quotients $\text{HQ}(\mathcal{E})$ is a small complete lattice.*

2.2. Local state classifiers. We recall the description of $\text{HQ}(\mathcal{E})$ given in [Hor24a].

Definition 2.3. We adopt the following definitions:

- A **local state classifier** of a category $\mathcal{C}$ is the colimit of all monomorphisms

$$\Xi := \text{colim} (\mathcal{C}_{\text{mono}} \rightarrow \mathcal{C}),$$

where $\mathcal{C}_{\text{mono}}$ denotes the subcategory consisting of all objects and all monomorphisms of $\mathcal{C}$.

- Its associated cocone is denoted by $\{\xi_X: X \rightarrow \Xi\}_{X \in \text{ob}(\mathcal{C})}$.

Fact 2.4 ([Hor24a]). *For a Grothendieck topos $\mathcal{E}$, we have the following facts:*

- $\mathcal{E}$ has a local state classifier Ξ .
- Ξ admits the canonical $\wedge$ -semilattice structure such that

$$\begin{array}{ccc} & X \times Y & \\ \xi_X \times \xi_Y \swarrow & & \searrow \xi_{X \times Y} \\ \Xi \times \Xi & \xrightarrow{\quad \wedge \quad} & \Xi \end{array}$$

commutes for every pair of objects (X, Y) .

- The complete lattice of internal filters of Ξ , denoted by $\text{Filt}(\Xi)$, is isomorphic to $\text{HQ}(\mathcal{E})$:

$$\text{HQ}(\mathcal{E}) \cong \text{Filt}(\Xi).$$

- For an internal filter $F \mapsto \Xi$, the counit $\epsilon_X: f^* f_* X \mapsto X$ of the associated geometric morphism $f: \mathcal{E} \rightarrow \mathcal{F}$ is given by the pullback diagram

$$\begin{array}{ccc} f^* f_* X & \longrightarrow & F \\ \downarrow \epsilon_X & \lrcorner & \downarrow \\ X & \xrightarrow{\xi_X} & \Xi. \end{array}$$

2.3. The local state classifier of $\Sigma\text{-Set}$. This section describes the local state classifier of the topos $\Sigma\text{-Set}$.

Definition 2.5. We introduce the notion of right congruences:

- A **right congruence** on Σ^* is an equivalence relation $\sim$ such that for any $u, v, w \in \Sigma^*$, if $u \sim v$ then $uw \sim vw$.
- For two congruences $\sim$ and $\sim'$, the order relation $\sim \leq \sim'$ means that $u \sim v$ implies $u \sim' v$ for any $u, v \in \Sigma^*$.
- The poset of all right congruences on Σ^* and their order is denoted by Ξ .
- The action of $\sim * w$ is defined by $u (\sim * w) v$ if and only if $wu \sim vw$.

Proposition 2.6. We have the following properties:

- These data make Ξ an internal semilattice in the topos $\Sigma\text{-Set}$. Furthermore, this is the local state classifier [Hor24a] of the topos $\Sigma\text{-Set}$.
- In other words, the Σ -set Ξ is the colimit of all monomorphisms in $\Sigma\text{-Set}$.
- The colimit cocone $\{\xi_X: X = (Q, \delta) \rightarrow \Xi\}_{X \in \text{ob}(\Sigma\text{-Set})}$ is given by

$$w (\xi_X(q)) v \iff qw = qv.$$

In particular, the morphism $\xi_{\mathcal{L}}: \mathcal{L} \rightarrow \Xi$ captures the notion of Nerode congruence.

Lemma 2.7. The component of the colimit cocone $\xi_{\mathcal{L}}: \mathcal{L} \rightarrow \Xi$ sends a language L to its Nerode congruence $\sim_L$, where

$$u \sim_L v \iff u^{-1}L = v^{-1}L.$$

Proposition 2.8 ([Hor24a] for $\Sigma\text{-Set}$). There is a bijective correspondence between equivalence classes of hyperconnected geometric morphisms from $\Sigma\text{-Set}$ and the internal filters of Ξ , which furthermore correspond to subsets $F \subset \Xi$ such that

- F is closed under Σ^* -actions:

$$\forall \sim \in F, \forall w \in \Sigma^*, (\sim * w) \in F.$$

- F contains the universal relation $\Sigma^* \times \Sigma^*$, the top element of Ξ , and is closed under finite intersections:

$$\forall \sim, \sim' \in F, (\sim \wedge \sim') \in F.$$

- F is upward closed:

$$\forall \sim \in F, \forall \sim' \in \Xi, (\sim \leq \sim' \implies \sim' \in F).$$

For a hyperconnected geometric morphism $h: \Sigma\text{-Set} \rightarrow \mathcal{E}$, let F_h denote the corresponding internal filter of Ξ .

Example 2.9. For the hyperconnected geometric morphism $h: \Sigma\text{-Set} \rightarrow \Sigma\text{-Set}_{\text{o.f.}}$, the corresponding filter F_h is the set of all congruences $\sim$ whose quotient set $\Sigma^*/\sim$ is finite.

3. LANGUAGE RECOGNITION AND SYNTACTIC TOPOI

3.1. Language recognition by a hyperconnected geometric morphism.

Proposition 3.1 (Equivalent definitions of recognition). *For a hyperconnected geometric morphism $h: \Sigma\text{-Set} \rightarrow \mathcal{E}$ and a language $L \in \mathcal{L}$, the following conditions are equivalent:*

- (1) L is an element of $h^*h_*\mathcal{L} \subset \mathcal{L}$.
- (2) The corresponding filter F_h contains the Nerode congruence $\sim_L$ of L .

Proof. By Fact 2.4, we have the pullback diagram

$$\begin{array}{ccc} h^*h_*\mathcal{L} & \longrightarrow & F_h \\ \downarrow \epsilon_{\mathcal{L}} \lrcorner & & \downarrow \\ \mathcal{L} & \xrightarrow{\xi_{\mathcal{L}}} & \Xi. \end{array}$$

This and Lemma 2.7 prove the equivalence. $\square$

Definition 3.2. We say that a hyperconnected geometric morphism $h: \Sigma\text{-Set} \rightarrow \mathcal{E}$ **recognizes** a language $L \in \mathcal{L}$ if it satisfies the equivalent conditions of Proposition 3.1. The set of languages recognized by h is denoted by $\mathbb{L}_h$.

The set $\mathbb{L}_h$ is the sub- Σ -set $\mathbb{L}_h = h^*h_*\mathcal{L} \rightarrow \mathcal{L}$ constructed by the pullback diagram

$$\begin{array}{ccc} \mathbb{L}_h = h^*h_*\mathcal{L} & \longrightarrow & F_h \\ \downarrow \epsilon_{\mathcal{L}} \lrcorner & & \downarrow \\ \mathcal{L} & \xrightarrow{\xi_{\mathcal{L}}} & \Xi. \end{array}$$

3.2. The syntactic Grothendieck topos associated with a language class.

Definition 3.3. A **language class** is a subset $C \subset \mathcal{L}$ of the set of languages $\mathcal{L}$.

Definition 3.4. For a language class $C \subset \mathcal{L}$, its **syntactic Grothendieck topos** $\mathcal{T}(C)$ is the minimum hyperconnected quotient that recognizes all languages in C .

For a language $L \in \mathcal{L}$, we call $\mathcal{T}(\{L\})$ the syntactic topos of L and write $\mathcal{T}(L)$ for $\mathcal{T}(\{L\})$ when no confusion can arise.

Remark 3.5 ($\mathcal{T}(C)$ is a geometric morphism). Rigorously speaking, $\mathcal{T}(C)$ is not just a topos, but a topos equipped with the canonical hyperconnected geometric morphism $h: \Sigma\text{-Set} \rightarrow \mathcal{T}(C)$.

Lemma 3.6. *For any family of right congruences $\{\sim_{\lambda}\}_{\lambda \in \Lambda}$, there exists a minimum internal filter that contains $\sim_{\lambda}$ for every $\lambda \in \Lambda$.*

Proof. Since an internal filter is defined by closure properties listed in Proposition 2.8, an arbitrary intersection of internal filters is again an internal filter. Therefore, the intersection of all internal filters that contain $\{\sim_{\lambda}\}_{\lambda \in \Lambda}$ is the minimum one. $\square$

Definition 3.7 (Generating an internal filter). For a family of right congruences $\{\sim_{\lambda}\}_{\lambda \in \Lambda}$, the minimum internal filter that contains them is denoted by

$$\langle \sim_{\lambda} \mid \lambda \in \Lambda \rangle.$$

Proposition 3.8 (Filter corresponding to $\mathcal{T}(C)$). *For a language class C , the internal filter $F_C \subset \Xi$ corresponding to the hyperconnected quotient $\Sigma\text{-Set} \rightarrow \mathcal{T}(C)$ is given by*

$$F_C = \langle \xi_{\mathcal{L}}(L) \mid L \in C \rangle.$$

Proof. By Proposition 3.1, the corresponding filter F_C is the minimum internal filter that contains $\xi_{\mathcal{L}}(L)$ for every $L \in C$. $\square$

ACKNOWLEDGEMENTS

The author thanks the Grothendieck Institute, Morgan Rogers, and Jérémie Marquès.
This work was supported by JSPS KAKENHI Grant Numbers JP24KJ0837 and JP26K24500.

USE OF AI

The author used AI tools to assist with writing this paper. The author takes full responsibility for its content.

REFERENCES

- [Hor24a] Ryuya Hora. “Internal parameterization of hyperconnected quotients”. *Theory and Applications of Categories* 42.11 (2024), pp. 263–313.
- [Hor24b] Ryuya Hora. *Topoi of automata I: Four topoi of automata and regular languages*. 2024. arXiv: [2411.06358](https://arxiv.org/abs/2411.06358) [[cs.FL](#)].
- [Joh81] Peter T. Johnstone. “Factorization theorems for geometric morphisms, I”. *Cahiers de topologie et géométrie différentielle* 22.1 (1981), pp. 3–17.
- [Joh02] Peter T. Johnstone. *Sketches of an Elephant: A Topos Theory Compendium, Volume 1*. Oxford University Press, 2002.
- [Law07] F. William Lawvere. “Axiomatic cohesion”. *Theory and Applications of Categories* 19.3 (2007), pp. 41–49.